

We are offering the wide range of water testing testers like pH , EC , TDS Testers

Same & equal to Hanna Instruments

<p>PHEP® PH TESTER</p> <p>RANGE PH : 0.0 TO 14.0 PH</p> <p>RESOLUTION PH : 0.1 PH</p> <p>ACCURACY PH : ±0.1 PH</p> <p>CALIBRATION : MANUAL, 2 POINTS</p> <p>BATTERY TYPE / LIFE : 4 X 1.5V / APPROX. 700 HOURS OF CONTINUOUS USE</p> <p>ENVIRONMENT : 0 TO 50°C (32 TO 122°F); RH MAX 95%</p> <p>DIMENSIONS : 175 X 41 X 23 MM (6.9 X 1.6 X 0.9")</p> <p>WEIGHT : 95 G (3.4 OZ.)</p> <p>SUPPLIED WITH PROTECTIVE CAP, CALIBRATION SCREWDRIVER, BATTERIES AND INSTRUCTIONS</p>	<p>DIST®1 TDS TESTER</p> <p>RANGE : 1999 PPM (MG/L)</p> <p>RESOLUTION : 1 PPM (MG/L)</p> <p>ACCURACY : ±2% F.S.</p> <p>TDS FACTOR : 0.5</p> <p>CALIBRATION SOLUTION : HI 70032</p> <p>CALIBRATION : MANUAL, 1 POINT</p> <p>PROBE : HI 73301</p> <p>TEMPERATURE COMPENSATION : AUTOMATIC, 0 TO 50°C (32 TO 122°F)</p> <p>BATTERY TYPE / LIFE : 4 X 1.5V / APPROX. 200 HOURS OF CONTINUOUS USE</p> <p>ENVIRONMENT : 0 TO 50°C (32 TO 122°F); RH MAX 95%</p> <p>DIMENSIONS : 175 X 41 X 23 MM (6.9 X 1.6 X 0.9")</p> <p>WEIGHT : 95 G (3.4 OZ.)</p> <p>SUPPLIED WITH PROTECTIVE CAP, SCREWDRIVER, BATTERIES AND INSTRUCTIONS.</p>	<p>DIST®2 TDS TESTER</p> <p>RANGE : 10.00 PPT (G/L)</p> <p>RESOLUTION : 0.01 PPT (G/L)</p> <p>ACCURACY : ±2% F.S.</p> <p>TDS FACTOR : 0.5</p> <p>CALIBRATION SOLUTION : HI 70038</p> <p>CALIBRATION : MANUAL, 1 POINT</p> <p>PROBE : HI 73302</p> <p>TEMPERATURE COMPENSATION : AUTOMATIC, 0 TO 50°C (32 TO 122°F)</p> <p>BATTERY TYPE / LIFE : 4 X 1.5V / APPROX. 200 HOURS OF CONTINUOUS USE</p> <p>ENVIRONMENT : 0 TO 50°C (32 TO 122°F); RH MAX 95%</p> <p>DIMENSIONS : 175 X 41 X 23 MM (6.9 X 1.6 X 0.9")</p> <p>WEIGHT : 95 G (3.4 OZ.)</p> <p>SUPPLIED WITH PROTECTIVE CAP, SCREWDRIVER, BATTERIES AND INSTRUCTIONS.</p>	<p>DIST®4 CONDUCTIVITY TESTER</p> <p>RANGE : 19.99 MS/CM</p> <p>RESOLUTION : 0.01 MS/CM</p> <p>ACCURACY : ±2% F.S.</p> <p>CALIBRATION : MANUAL, 1 POINT</p> <p>PROBE : HI 73304</p> <p>TEMPERATURE COMPENSATION : AUTOMATIC, 0 TO 50°C (32 TO 122°F)</p> <p>BATTERY TYPE / LIFE : 1.5V (4) / APPROX. 200 HOURS OF CONTINUOUS USE</p> <p>ENVIRONMENT : 0 TO 50°C (32 TO 122°F); RH MAX 95%</p> <p>DIMENSIONS : 175 X 41 X 23 MM (6.9 X 1.6 X 0.9")</p> <p>WEIGHT : 95 G (3.4 OZ.)</p> <p>SUPPLIED WITH PROTECTIVE CAP, SCREWDRIVER, BATTERIES AND INSTRUCTIONS.</p>
 <p>USD- 23/-</p>	 <p>USD- 23/-</p>	 <p>USD- 23/-</p>	 <p>USD- 23/-</p>

MINIMUM ORDER QUANTITY 25 PIECES OF EACH , WARRANTY 6 MONTHS



GABY INSTRUMENTS
COIMBATORE - 641005
INDIA.

gabyinstruments@gmail.com