

## IRON-50 Ex 230 VAC 0.18 kW · 50 l/min

**Liquids:**  **Diesel**  **Petrol**

IRON-50 Ex 230 VAC · 50 l/min

10035

- Self-suction - self-priming, explosionproof, eccentric with self-adjusting blades
- With recirculation bypass
- Suction: 2.7 m
- Priming pipe suction: 5 m
- Free flow: 50 l/min
- Consumption: 1-1.8 A
- Motor: 0.18 kW 230 VAC 50 Hz single-phase EExd
- With thermal protector
- 2,850 rpm
- S2 30' operation
- IP-55 protection
- Operation temperature: -10 °C · +40 °C
- Motor zone classification: II 2 G Ex dc IIB T4
- Certificate: 94/9/CE · LOM 15ATEX0124
- Thread connection: F1" (BSP) and flange
- ON/OFF switch
- 3 m cable
- Anti-rust treatment



### Size and weight (approx.):

- Dim.: 265x165x155 mm (length x width x height)
- Weight: 11.4 kg

SA-50 Ex 230 VAC · Pump with litre meter

**Liquids:**  **Diesel**  **Petrol**

IRON-50 Ex 230 VAC pump + MG-80AV mechanical aluminium meter with Viton joints

SA-50 Ex 230 VAC + MG-80AV

SA-50 Ex 230 VAC + MG-80AV + Base no. 4

31950-  
CF00000

33330-  
CF00000



*\*Hose and nozzle not included*

©2008 GESPASA · TOT COMERCIAL S.A. · NIF A25031154 · Partida Horta d'Amunt s/n · Apartat de Correus núm. 149 · 25600 · BALAGUER (Lleida) SPAIN

Tel.: ++34 (9)73 45 10 72 · Fax: ++34 (9)73 44 84 00 · [PRIVACY POLICY](#) · [www.cenics.net](http://www.cenics.net)