



## MEAT & DELI COUNTER---TOP OPEN ( PLUG IN)

Export model	SE-13MWOEL	SE-20MWOEL	SE-26MWOEL	SE-38MWOEL
Factory Model	IHC-1.3/120WA	IHC-2.0/120WA	IHC-2.6/120WA	IHC-3.8/120WA
Product code	2.1.10.04.604	2.1.10.04.602	2.1.10.04.603	2.1.10.04.605
Cabinet [mm] WxDxH \	1350*1185*880	1975*1185*880	2600*1185*880	3850*1185*880
Package [mm] WxDxH	1508*1343*1006	2133*1343*1006	2758*1343*1006	4008*1343*1006
Rated voltage/Rated frequency Hz	220VAC~240VAC, 50Hz	220VAC~240VAC, 50Hz	220VAC~240VAC, 50Hz	220VAC~240VAC, 50Hz
Climate class ( °C, %RH)	3 (25 °C, 60%RH)	3 (25 °C, 60%RH)	3 (25 °C, 60%RH)	3 (25 °C, 60%RH)
Product temperature	-1~5°C	-1~5°C	-1~5°C	-1~5°C
Net volume [L]	110	156	221	312
Total display area (TDA) [m	1.05	1.57	2.11	3.14
Rated current [A]	3	4	4.8	4.9
Rated power [W]	520	660	760	940
Net weight / Gross weight [Kg.]	110/140	170/245	210/295	310/365
Compressor	huayi ML90TG	huayi MP12RB	huayiMP14RB	secop SC18MLX.3
Refrigeration Capacity[W]	550	890	980	1520
Compressor Type	reciprocating	reciprocating	reciprocating	reciprocating
Refrigerant Qty [g]	800	950	1150	1400
Evaporating Temp (°C)	-15	-15	-15	-15
Power consumption [kWh/24h]	8.76	13.86	17.75	27.04
Refrigerant	R404A	R404A	R404A	R404A
Condenser	Copper pipe with Fin evaporator			
Evaporator	Copper pipe with Fin evaporator			
Condensor motorfan	saiwei 1*40W	saiwei 2*40W	saiwei 2*40W	saiwei 2*40W
Evaporator motorfan	jianzhun 2*14W	jianzhun 3*14W	jianzhun 3*14W	jianzhun 4*14W
Expansion valve	sanhua RFKA03E-3.4-10	sanhua RFKA03E-3.4-10	sanhua RFKA03E-3.4-10	sanhua RFKA03E-3.4-10
Thermostat	chunchang CC4611-06	chunchang CC4611-06	chunchang CC4611-06	chunchang CC4611-06
Light	T8 LED cold white 1*10W	T8 LED cold white 2*7W	T8 LED cold white 2*10W	T8 LED cold white 3*10W
Supports	no 4 (M18)	no 4 (M18)	no 4 (M18)	no 4 (M18)
Drainage	water tray/pour away	water tray/pour away	water tray/pour away	water tray/pour away
Inner tank bottom	Prepainted Steel	Prepainted Steel	Prepainted Steel	Prepainted Steel
Drawing type condensing	yes	yes	yes	yes
Inner material	Stainless Steel 201	Stainless Steel 201	Stainless Steel 201	Stainless Steel 201
Outer colours	White+Gray (RAL7024)			
Side panel L/R	Foaming Panel+tempered glass			
Loading quantity(40'HQ)	16	8	6	4

