

### The Technical Data For Tunnel Ovens

Sr. no	Type of Oven	Ideal for	Type of Conveyor	Useful width mm		Baking length mm
1	Direct Gas	Biscuits, Sponge Cake, Pizza, Crackers	Steel Band = Drum φ700 - 1000 Wire Mesh = Drum φ 1000	600 ÷ 1.600		Variable according to production needs
2	Cyclothermic	Biscuits	Steel Band = Drum φ700 - 1000 Wire Mesh = Drum φ 1000	600 ÷ 1.600	10.000 ÷ 16.000	Length and combustion Chambers number can be increased according to needs
		Sponge cake			16.000 ÷ 25.000	
Confectionery		25.000 ÷ 36.000				
		Bread	Lateral Chains = Metal Plates / Wire Mesh Stone	1.000 ÷ 3.000	36.000 ÷ 46.000	
3	Hybrid	Biscuits	Steel Band = Drum φ700 - 1000	600 ÷ 1.600		The Length of Direct Gas Oven Section and Cyclothermic one are calculated according to Production needs
		Crackers	Wire Mesh = Drum φ 1000			
4	Convection	Biscuits Sponge cake Confectionery	Steel Band = Drum φ700 - 1000 Wire Mesh = Drum φ 1000	600 ÷ 1.600	10.000 ÷ 16.000 16.000 ÷ 25.000	Length and combustion Chambers number can be increased according to needs
5	Tunnel Ovens for Bread					
	Electric	Bread	Lateral Chains = Metal Plates/Wire mesh Stone	1.000 ÷ 3.000		Variable according to Procuction needs
	Cyclothermic	Bread	Lateral Chains = Metal Plates/Wire mesh Stone	1.000 ÷ 3.000	10.000 ÷ 16.000 16.000 ÷ 25.000 25.000 ÷ 36.000 36.000 ÷ 46.000	Length and combustion Chambers number can be increased according to needs